Summit[®] 3000 Low-Profile Floor Scale



APPROVALS





The load cell cable exits weldment toward the interior of scale, allowing flexibility to route it out any side of scale to digital weight indicator.

PART NUMBER/PRICE

STANDARD FEATURES

- Four NTEP Certified alloy steel shear beam load cells
- Top access junction box
- Rugged diamond safety tread plate steel deck
- Four adjustable rigid polyurethane rubber feet, 3 in (76.2 mm) diameter

SPECIFICATIONS

End Load Capacity:

100% full scale at 2,000 lb and 5,000 lb 80% full scale at 10,000 lb

Cable Length:

20 ft (6.1 m) (for connecting junction box to indicator)

- Signal trim summing board housed in ABS enclosure
- Threaded eyebolt hole (1/2–13NC) located in center of the deck for easy lifting
- 20 ft of EL147 load cell cable

Warranty:

Summit 3000 weldment and load cells two years, all other components one year

Approvals:

NTEP CC 92-001A9, Class III 5,000d Measurement Canada AM-5530, Class III 5,000d

	NOMBER/PRICE			
PART #	SIZE (W X L X H)*	CAPACITY	EST. SHIP WEIGHT	PRICE
Single Sca				
74715	3ft x 3ft x 3.625 in	2,000 lb	190 lb	Consult
74716	4ft x 4ft x 3.625 in	2,000 lb	305 lb	Consult
74717	4ft x 4ft x 3.625 in	5,000 lb	305 lb	Consult
74718	4ft x 4ft x 3.625 in	10,000 lb	305 lb	Consult
74719	4ft x 5ft x 3.625 in	5,000 lb	395 lb	Consult
74720	4 ft x 5 ft x 3.625 in	10,000 lb	445 lb	Consult
74721	4ft x 6ft x 3.625 in	5,000 lb	470 lb	Consult
74722	4ft x 6ft x 3.625 in	10,000 lb	525 lb	Consult
74723	5 ft x 5 ft x 3.625 in	5,000 lb	505 lb	Consult
74724	5 ft x 5 ft x 3.625 in	10,000 lb	575 lb	Consult
Single Sca	le-Canadian Weights and Measures Certified			
77440	3 ft x 3 ft x 3.625 in	1,000 kg	190 lb	Consult
77373	4 ft x 4 ft x 3.625 in	1,000 kg	305 lb	Consult
77346	4ft x 4ft x 3.625 in	2,500 kg	305 lb	Consult
77347	4ft x 4ft x 3.625 in	5,000 kg	305 lb	Consult
82880	4 ft x 5 ft x 3.625 in	2,500 kg	395 lb	Consult
82881	4 ft x 5 ft x 3.625 in	5,000 kg	445 lb	Consult
77348	5 ft x 5 ft x 3.625 in	2,500 kg	505 lb	Consult
77349	5 ft x 5 ft x 3.625 in	5,000 kg	575 lb	Consult
5-Scale Pa	ckage			
75809	3 ft x 3 ft x 3.625 in	2,000 lb	850 lb	Consult
75810	4ft x 4ft x 3.625 in	2,000 lb	1,400 lb	Consult
75811	4ft x 4ft x 3.625 in	5,000 lb	1,400 lb	Consult
75812	4ft x 4ft x 3.625 in	10,000 lb	1,400 lb	Consult
75813	4ft x 5ft x 3.625 in	5,000 lb	1,870 lb	Consult
75814	4 ft x 5 ft x 3.625 in	10,000 lb	2,115 lb	Consult
75815	4ft x 6ft x 3.625 in	5,000 lb	2,210 lb	Consult
75816	4ft x 6ft x 3.625 in	10,000 lb	2,495 lb	Consult
75817	5 ft x 5 ft x 3.625 in	5,000 lb	2,325 lb	Consult
75818	5 ft x 5 ft x 3.625 in	10,000 lb	2,675 lb	Consult
5-Scale-C	anadian Weights and Measures Certified			
77472	3 ft x 3 ft x 3.625 in	1,000 kg	850 lb	Consult
77473	4ft x 4ft x 3.625 in	1,000 kg	1,400 lb	Consult
77474	4ft x 4ft x 3.625 in	2,500 kg	1,400 lb	Consult
77475	4ft x 4ft x 3.625 in	5,000 kg	1,400 lb	Consult
82885	4ft x 5ft x 3.625 in	2,500 kg	1,870 lb	Consult
82886	4ft x 5ft x 3.625 in	5,000 kg	2,115 lb	Consult
77476	5ft x 5ft x 3.625 in	2,500 kg	2,325 lb	Consult
77477	5ft x 5ft x 3.625 in	5.000 kg	2,675 lb	Consult

📕 🕈 An ISO 9001 Registered Company © 2014 Rice Lake Weighing Systems 01/14 Prices and specifications subject to change without notice. Visit ricelake.com for current prices.

Summit[®] 3000 Low-Profile Floor Scale

OPTIONS/ACCESSORIES

DESCRIPTION	EST. SHIP WEIGHT	PRICE
Floor anchor plates, mild steel (set of two)	—	Consult
Top access foot adjust holes	—	Consult
nps		
3ft x 3ft x 3.625 in	133 lb	Consult
4ft x 3ft x 3.625 in	177 lb	Consult
5ft x 3ft x 3.625 in	226 lb	Consult
3ft x 4ft x 3.625 in	177 lb	Consult
4ft x 4ft x 3.625 in	224 lb	Consult
5ft x 4ft x 3.625in	272 lb	Consult
3ft x 3ft	100 lb	Consult
4ft x 4ft	125 lb	Consult
5ft x 5ft	155 lb	Consult
4ft x 5ft	140 lb	Consult
4 ft x 6 ft	157 lb	Consult
	Floor anchor plates, mild steel (set of two) Top access foot adjust holes nps 3ft x 3ft x 3.625 in 5ft x 3ft x 3.625 in 5ft x 3ft x 3.625 in 3ft x 4ft x 3.625 in 3ft x 4ft x 3.625 in 5ft x 4ft x 3.625 in 3ft x 4ft x 3.625 in 5ft x 4ft x 3.625 in	Floor anchor plates, mild steel (set of two) — — Top access foot adjust holes — — nps

* For custom sizes or capacities please consult factory for RoughDeck^{\circledast} HP pricing

** For use with DC-190 counting scales ***Not recommended for use with pallet jacks

